

IVECO DAILY - TRACTOR CONVERSION SPECIFICATIONS

BE-Combi is brand-independent and achieves maximum payload for the most popular commercial vehicle brands. Below you'll find an overview of the specifications for the Iveco Daily, which is also available as a download at the bottom of the page.



IVECO DAILY 40C and 50C

The model must be factory fitted with these options	Code
Digital Smart Tachograph	00821
13-pin connector	06520
Heavy duty dynamo 220 Amp.	72837
Bodybuilder connector for surface mounting (only for double cabin)	08656
Seven-leaf spring package, semi-elliptical (standard at 40C)	02240
No spare wheel	02213
No spare wheel carrier	00724
Without rear bumper	00169
AdBlue tank under the cabin	79250
Rear view camera supplied separately	00344
Without parking sensors	06327
Blind spot radar on cabin (not for N1)	01713
Exterior mirrors on extended arm (width 2,350 mm.)	73024
Please note: Order 4.44 rear axle	00003
Adaptive cruise control can be ordered	
Motorization: 2.3 liter 40C16 light duty or 3.0 liter 40C18 heavy duty	
When converting a tractor, only a rear-wheel drive chassis is used, with double-tyre mounting at the rear	

BE-COMBI TRACTOR CONVERSION OPTIONS

Tractor conversion

Single cab, wheelbase 3,000 mm

Double cab, wheelbase 3,750 mm

Available options

Power supply Harrison or Clang for tail lift, winch or 2nd battery

Side skirts with aluminium plate, side skirts in standard white color

Side skirts in RAL color

Side skirts in Metallic color

Spoiler and side fenders

General conditions

Delivery time In consultation (after delivery of chassis approx. 4 to 6 weeks)

Delivery By the dealer in Vuren (transport by BE-Combi in consultation)

Warranty 12 months (after the vehicle has been put into service)

Other Our general terms and conditions of delivery apply to all products supplied by BE-Combi.

BE-Combi International B.V.

Azewijnseweg 12

4214 KC Vuren

+31 (0) 345 - 633 644

verkoop@be-combi.nl

www.be-combi.com