# MAN TGE - 3500PLUS SPECIFICATIONS

BE?Combi is brand?independent and delivers maximum payload capacity for the most well?known commercial vehicle brands. Below you will find an overview of the specifications for the MAN TGE, which is also available for download at the bottom of the page.

## MAN TGE

| MAN TGE 5.0 T must be equipped with the following options | Code |
|---|---|
| Multifunctional control unit | IS2 |
| Front axle 2.100 kg. | VV8 |
| Suspension / Damping reinforced | 2MR / 2MT |
| AGM batterie with bigger capacity | NY4 |
| Rearview mirrors with extended bracket > 2.160 mm. | 3BL / 3AQ |
| Digital Tachograph | 9NI |
| Preparation towing hook | 1D7 |
| If 1D7 not available, order complete towing hook | 1D1 |
| Snelheidsbegrenzer op 100 km/h | 7H2 |
| Position lights on cabin roof | 6S3 |
| Registration as 3,5 ton | 07H |
| Incomplete N1 homologation | 5ET |
| Rear lights with longer cables | 8SE |
| Speed limiter 100 km/u | 7H2 |
| Voertuig aanleveren met uitgeschakelde transport modus | 2A7 |
| Without parking sensors | 7X0 |
| Preparation rear view camera | KA8 |
| Without blind spot radar | BR0 |
| Tranportmodus deactivated | 2A7 |
| Extra battery always in combination with option IS2 | |
| Automatic gearbox recommended | n/a |
| Engine minimum 120 kW | n/a |

# Options BE-combi 3500PLUS systeem

| Wheelbase | Maximum body length | Minimum body length plus tail lift | Minimum body length no tail lift |
|---|---|---|---|
| 3.640 mm | 4.700 mm | 4.700 mm | 4.500 mm |
| 4.490 mm | 5.200 mm | 5.200 mm | 5.200 mm |

## Information for the body builder

- Tail lift capacity max. 1.000 kg.
- The trailer is delivered without legally required lighting and rear bumper
- Connections such as cooling machine, hydraulics or other connections must **always be disconnectable**.


## BE-Combi Sales & Rental B.V.

Azewijnseweg 12

4214 KC Vuren

+31 (0) 345 - 633 644

verkoop@be-combi.nl

www.be-combi.nl